

Construction Specialties

Louvers





Compare Louvers

PRODUCT FAMILY	STANDARD NON-DRAINABLE	DRAINABLE	STORM-RESISTANT	BOLD LINE	PERFORM
# of Models	8	7	15	2	3
Louver Depth	1"- 6"	2'' - 6''	2"- 9"	6" - 7"	7"
Continious Line	•	•	•	٠	
Mullion	•	•	•	٠	
Vertical Orientation			•		•
Horizontial Orientation	•	•	•	•	•
Sightproof			•	•	•
Customizeable	•	•	•	٠	•
Bold Line	•		•	•	
Perform	•		•		•
Rain Defense	Good	Good	Best	Good	Better
CENTRIA Integration	•	•	•	٠	•

EXTREME-WEATHER	BLAST-RESISTANT	THINLINE	ACOUSTICAL	OPERABLE
9	10	5	7	3
4"- 9"	4"- 9"	1¾" - 2¼"	6"-12"	4"- 6"
•	•	•	•	
•	•	•	•	•
•	•			
•	•	•	•	•
•	•		•	
•	•	•	•	•
	•			
•				
Best	Better	Good	Good	Good
•	•			

FAMILY	MODEL	DADE COUNTY CERTIFICATION		AMCA CE	RTIFICATION		
	MODEL	Notice of Acceptance (NOA) Includes TAS 201, 202, 203	Point of Beginning Water Penetration	Wind-driven Rain 3" rain at 29 mph	Wind-driven Rain 8'' at 50 mph	Pressure Drop	Acoustics
Extreme-Weather	DC-4174	•	٠			•	
Extreme-Weather	DC-6174	•	٠			•	
Extreme-Weather	DC-5304	•		•		•	
Extreme-Weather	DCV-5704	•		•	•	•	
Extreme-Weather	DCH-5704	•	٠	•	•	•	
Extreme-Weather	DC-9614	•		•	•	•	
Extreme-Weather	DC-6804	•	٠	•	•	•	
Extreme-Weather	EW-5210		•			•	
Storm-Resistant	RS-2300			•		•	
Storm-Resistant	RS-3700		•	•	•	•	
Storm-Resistant	RS-4700		٠	•	٠	•	
Storm-Resistant	RS-5300			•		•	
Storm-Resistant	RSH-5700		٠	•	•	•	
Storm-Resistant	RS-5900		٠	•	•	•	
Storm-Resistant	RS-7315			•		•	
Storm-Resistant	RS-7305			•		•	
Storm-Resistant	RS-7705		٠	•		•	
Storm-Resistant	RS-8615			•	•	•	
Storm-Resistant	RS-9615				•	•	
Storm-Resistant	RS-4600*			•		•	
Storm-Resistant	RS-4605			•	•	•	
Storm-Resistant	RS-5605				•	•	
Storm-Resistant	B-7505		•	•	•	•	
Storm-Resistant	RSV-5700			•	٠	•	
Storm-Resistant	RS-5800		٠	•	٠	•	

AMCA-540 Basic AMCA-540 Enhanced AMCA-55 • ٠ ٠ . • • ۲ ٠ ٠

AMCA LISTING

*Tested in accordance with AMCA but not AMCA certified.

	FEMA 361
50	ICC-500
	•

Testing & Certification Resources:

Dade County: https://www.miamidade. gov/building/testing.asp

AMCA: https://amca.org

FEMA:

Highlights of ICC 500-2014, ICC/NSSA Standard for the Design and Construction of Storm Shelters (https://www.fema.gov/sites/default/ files/2020-07/highlights-icc-500.pdf)

FEMA:

Safe Rooms for Tornadoes and Hurricanes (https://www.fema.gov/sites/default/files/ documents/fema_safe-rooms-for-tornadoes-and-hurricanes_p-361.pdf)

Testing matrix all models, continued.

FAMILY	MODEL	DADE COUNTY CERTIFICATION	ΑΜϹΑ ϹΕ		RTIFICATION		
	MODEL	Notice of Acceptance (NOA) Includes TAS 201, 202, 203	Point of Beginning Water Penetration	Wind-driven Rain 3" rain at 29 mph	Wind-driven Rain 8'' at 50 mph	Pressure Drop	Acoustics
Drainable	A4097		•			٠	
Drainable	A4177		•			٠	
Drainable	A6097		•			•	
Drainable	A6177		•			•	
Drainable	A6155		•			•	
Drainable	A2097		•			•	
Drainable	B5157		•			•	
Drainable	GS-407		•			•	
Drainable	GS-607		•			•	
Bold Line	B-6485		•			•	
Bold Line	B-7505		•	•	•	•	
Perform	PL-3600*			•	•	•	
Perform	PL-4080*			•		٠	
Perform	PL-5700*			•	•	•	
Non-Drainable	GS-410*		•			•	
Non-Drainable	GS-610		•			•	
Non-Drainable	A4080/A4085		•			•	
Non-Drainable	A4100		•			٠	
Non-Drainable	A4105		•			٠	
Non-Drainable	4180*					•	
Non-Drainable	A6080/A6085		•			٠	
Non-Drainable	A6100*		•			•	
Non-Drainable	A6105*		•			٠	

	AMCA LISTING		FEMA 361
AMCA-540 Basic	AMCA-540 Enhanced	AMCA-550	ICC-500

*Tested in accordance with AMCA but not AMCA certified.

Testing matrix all models, continued.

FAMILY	MODEL	DADE COUNTY CERTIFICATION			AMCA CERTIFICATION		
	MODEL	Notice of Acceptance (NOA) Includes TAS 201, 202, 203	Point of Beginning Water Penetration	Wind-driven Rain 3" rain at 29 mph	Wind-driven Rain 8" at 50 mph	Pressure Drop	Acoustics
Blast-Resistant	BL-4179		•			•	
Blast-Resistant	BL-6179		•			•	
Blast-Resistant	BL-4089		•			•	
Blast-Resistant	BL-6089		•			•	
Blast-Resistant	BLH-5709		•	•	•	٠	
Blast-Resistant	BLV-5709			•	•	•	
Blast-Resistant	BL-6809		•	•	•	•	
Blast Resistant	BL-5609				•	•	
Blast-Resistant	BL-5809		•	•	•	•	
Blast-Resistant	BL-7709		•	•		•	
Thinline	2282*					•	
Thinline	2252*					•	
Thinline	1302*					•	
Acoustical	A-12350*		•			•	•
Acoustical	A-12360*		•			•	•
Acoustical	A-12370*		•			•	•
Acoustical	A-6370*		•			•	•
Acoustical	A-8370*		•			•	•
Acoustical	A-12970*		•			•	•
Acoustical	A-8860*		•			•	•
Operating	6870*					•	
Operating	6917*		•			•	
Operating	4830*					•	

AMCA	LISTING	

	FEMA 361		
AMCA-540 Basic	AMCA-540 Enhanced	AMCA-550	ICC-500
	•	•	
	•	•	

*Tested in accordance with AMCA but not AMCA certified.



c-sgroup.com | 800.233.8493